



JLT1214 for Logistics & Warehousing

# Logistics Computer that Reduces Total Cost of Ownership and Improves Productivity

The JLT1214P and JLT1214N computers are the latest generation logistics computers from JLT. With proven reliability and the latest processor technology, they deliver the lowest total cost of ownership for a wide variety of logistics applications. They have an integrated 9-36 VDC power supply, but are also available with an isolated 18-60 VDC for electrical truck and forklift installations.

#### **Virtually Unbreakable Touch Screen**

The JLT1214P computer features the revolutionary JLT PowerTouch™ display technology, providing a familiar, user-friendly experience comparable to modern consumer devices, both with a gloved or ungloved hand, while ensuring ruggedness, reliability and longevity in even the most demanding environments. Thanks to a 64-bit Intel® quad-core processor, the JLT1214P also offers enhanced computing performance. The combination of the new user-friendly touch screen and the higher performance speeds up tasks and increases users' productivity.

#### **Proven Reliability**

The JLT1214P and JLT1214N computers are reliable workhorses based on the successful JLT computer platform that has been tested in the field by customers around the globe for many years. It is designed from the bottom up with the latest processor technology to deliver maximum reliability and trouble free operation in very tough environments, from cold storage rooms to broiling hot sun, from fixed wall mounts to vibrating forklifts.

#### **Lowest Total Cost of Ownership**

Both computers integrate all essential features required for a simple, quick, and cost effective installation. Moreover, they are highly reliable without additional add-ons and cables.

#### **Key Features**

- JLT PowerTouch™ display technology with hardened glass for outstanding resistance to wear and tear reduces disruptive computer downtime
- Everything built in for lowest cost and highest reliability
- Dual diversity PIFA WLAN antennas, custom-made for reliable WiFi in environments with poor coverage
- Integrated isolated DC/DC secured operation in spite of unstable voltage
- Pressure equalization membrane operation in temperatures from -30 to +55 degrees C
- 12" XGA LED display with the smallest footprint in its class

#### **User Examples**

- Warehousing
- Transportation
- Manufacturing

**Because it Works!™** 

## **JLT1214 Product Specifications**

Base Unit	
Processor	Quad core Intel® E3845
Memory	4GB DDR 3
Display	12.1" XGA LED 500 NIT
	JLT1214P Capacitive touch screen with JLT PowerTouch™ technology
	JLT1214N Resistive 4-wire touch screen
Storage	
SATA	CFast 16GB, 32GB, 64GB, 128GB
RF Option	S
Radio	Dualband WLAN 802.11 ac, MU-MIMO supported
	Bluetooth v4.2
Antennas	WLAN dual diversity antennas (PIFA)
	User configurable external or internal WLAN and Bluetooth antennas
Interfaces	
Ports	4x USB 2.0
	1x Ethernet 10/100/1000
	1x RS232 with 5V
Speakers	Waterproof stereo speakers
	HD Audio

Power Supply			
Input	18-60 VDC Isolated		
	9-36 VDC Unisolated		
UPS	Internal battery for graceful shut down at unexpected power outages		
Operating Systems			
Windows	Windows 10		
	Windows Embedded Standard 7		
	Windows 7		
Physical Characteristics			
Dimensions and weight	305mm (w) x 240mm (h) x 59mm (d) 12 inch (w) x 9.4 inch (h) x 2.3 inch (d)		
<b>2</b>			
<b>2</b>	12 inch (w) x 9.4 inch (h) x 2.3 inch (d)		
weight	12 inch (w) x 9.4 inch (h) x 2.3 inch (d)		
weight	12 inch (w) x 9.4 inch (h) x 2.3 inch (d) Weight: 3.5 kg, 7.7 LB		
Environment Operating temp.	12 inch (w) x 9.4 inch (h) x 2.3 inch (d) Weight: 3.5 kg, 7.7 LB  -30° C to 55° C		
Environment Operating temp. Storage temp.	12 inch (w) x 9.4 inch (h) x 2.3 inch (d) Weight: 3.5 kg, 7.7 LB  -30° C to 55° C  -35° C to 75° C		
Environment Operating temp. Storage temp. Connector Sealing	12 inch (w) x 9.4 inch (h) x 2.3 inch (d) Weight: 3.5 kg, 7.7 LB  -30° C to 55° C  -35° C to 75° C  Roxtec sealing cable protection (optional)		
Environment Operating temp. Storage temp. Connector Sealing Humidity	12 inch (w) x 9.4 inch (h) x 2.3 inch (d) Weight: 3.5 kg, 7.7 LB  -30° C to 55° C  -35° C to 75° C  Roxtec sealing cable protection (optional) 10–95% RH		
Environment Operating temp. Storage temp. Connector Sealing Humidity Dust and water	12 inch (w) x 9.4 inch (h) x 2.3 inch (d) Weight: 3.5 kg, 7.7 LB  -30° C to 55° C  -35° C to 75° C  Roxtec sealing cable protection (optional) 10–95% RH  IP65 - IEC 60529:2001		

### **Accessories**







RAM® VESA75-mount



**Keyboard Bracket** 



**Fully Sealed Keyboard** 



JLT:Care Service Level Agreement

#### **JLT Mobile Computers**

Head Office: Isbjörnsvägen 3, SE-352 45 Växjö, SWEDEN
Sales Office: Medborgarplatsen 3, Plan 8, SE-118 26 Stockholm, SWEDEN
Phone: +46 470 53 03 00 Fax: +46 470 445 29 Email: info@jltmobile.com
North America: 7402 West Detroit Street, Suite 150 Chandler, Arizona 85284, USA

**Toll free US**: 844-705-4200 **Intl Phone:** +1 480 705 4200 **Fax:** +1 480 397 1214 **Mail:** USsales@jltmobile.com www.jltmobile.com

